

INDUSTRIAL SOLUTIONS



CONRAC 6018 ID

18" LCD/TFT Industrial Display

CONRAC's 6018 ID high resolution multi frequency industrial LCD/TFT-display is supplied in an attractive metal housing or in rack/console mount version.

CONRAC GmbH stands for High Performance Displays for specific applications. Own R&D, production and service at the German headquarters guarantee highest quality standards.

The use of high grade industrial components, modular construction, robust aluminium casing and special laminated safety glass panel with high efficiency anti-glare treatment make the displays the perfect choice for 24h operation in demanding applications.

FEATURES

Robust aluminium housing

Specially designed for use in rough industrial environment

Safety glass with high efficiency anti-glare treatment

Superior legibility and safety, reduced EMI for healthier working environment

Universal proprietary controller

Flexible solutions (VGA, CVBS and S-Video inputs), extra wide frequency range (15kHz – 85kHz)

High contrast and flicker-free image

Reduced strain for the user's eyes

Enhanced shock & vibration resistance

High lifetime in critical ambient conditions

Integrated counter for hours of operation

Easy to plan maintenance

Conrac electronics and design

In-house R&D ensures long term availability

DISPLAY

Panel type:	Full colour active matrix TFT
Size / Active screen dimensions:	18.1" – 46cm / 359mm (horizontal) x 287mm (vertical)
Resolution:	Multiscan up to 1280 x 1024 (SXGA)
Horizontal frequency:	15 – 85kHz
Vertical frequency:	50 – 85Hz
Pixelclock:	Up to 140MHz
Video	15.7kHz CVBS / Y/C video
Brightness (typical):	260 cd/m ² with glass panel (95% light transmission)
Contrast ratio:	400:1 typical
Number of colours:	16.7 Mio colours
Viewing angle:	±80° horizontal and vertical
Backlight:	Cold cathode fluorescent lamp (CCFL)
Lamp life time:	50,000 hours @ 25°C ambient temperature, continuous operation

SIGNAL INPUT / CONNECTORS / SYNCRONISATION

PC / video signal input:	PC analog, CVBS, Y/C (PAL, SECAM, NTSC)						
Connectors:	<table border="0"> <tr> <td>RGB (PC) input:</td> <td>1 x 15 pin HD-Sub</td> </tr> <tr> <td>CVBS:</td> <td>2 x Cinch</td> </tr> <tr> <td>Y/C:</td> <td>1 x Mini DIN</td> </tr> </table>	RGB (PC) input:	1 x 15 pin HD-Sub	CVBS:	2 x Cinch	Y/C:	1 x Mini DIN
RGB (PC) input:	1 x 15 pin HD-Sub						
CVBS:	2 x Cinch						
Y/C:	1 x Mini DIN						
Synchronization:	Sync on green, Composite sync with auto detect Separate H- and V-sync						

CONTROLS

Keypad and on screen menu

ENVIRONMENTAL CONDITIONS

Temperature (operating):	0°C - +45°C
Temperature (non-operating):	-20°C - +60°C

POWER

Power supply:	115V / 230V ±10%, automatic selection
Power consumption:	60W, 10W in sleep mode

APPROVALS

EMI/EMC:	EN55022 class A, EN55024
Safety:	EN60950, UL 1950, CE

SUPPLIED ACCESSORIES

VGA cable (15pin) 2m, AC power cord 2.5m	
Operating Manual	
Cabinet version only:	Bracket (desk stand, wall and ceiling mount)

STANDARD COLOUR

Standard colour cabinet/front panel:	RAL 9005 (deep black), non-structured
--------------------------------------	---------------------------------------

VERSIONS

6018 ID Cabinet version

Ultra slim metal design housing (IP21) supplied with bracket for wall or ceiling mounting or to be used as desk stand.
Prepared for mounting according to VESA specification.

H x W x D: 345mm x 449mm x 89mm
Weight: 9kg

**6018 ID Rack Mount version**

Rack/console mount configuration with IP65 front (8U).

H x W x D: 354mm x 483mm x 91mm
Weight: 10kg

**OEM versions**

Customized versions available on request.

OPTIONS*

*Please note: Not all options may be combined.

Cabinet & Rack mount version only:

24V DC power supply operating from 18V to 32V

Technical specification subject to change without prior notice. GM 260.0243, is_6018id_rev07

Headquarters:

CONRAC GmbH - Lindenstrasse 8 - D-97990 Weikersheim - Germany - Tel.: +49-7934-101 0 - Fax: +49-7934-101 101 - E-mail: info@conrac.de - www.conrac.de

Subsidiaries & Sales Offices:

CONRAC France - 7 rue Saint Christophe - 60300 Baron - France - Tel.: +33-3-44 54 96 99 - Fax: +33-3-44 58 55 09 - E-mail: info@conracfrance.fr - www.conrac.fr

CONRAC Sales Office Northern Europe - Pölsjögatan 66 - S-25440 Helsingborg - Sweden - Tel.: +46-42-212 939 - Fax: +46-42-212 948 - E-mail: info@conrac.se - www.conrac.se

CONRAC Sales Office Southern Europe - Via R. R. Garibaldi 30 - I-00145 Rome - Italy - Tel.: +39-06-45 43 92 02 - Fax: +39-06-45 43 91 79 - E-mail: info@conrac.it - www.conrac.it

CONRAC Asia Display Products Pte Ltd. - 82 Genting Lane #05-04 - Singapore 349567 - Tel.: +65-67 42 79 88 - Fax: +65-67 47 39 33 - E-mail: sales@conrac-asia.com - www.conrac-asia.com

CONRAC MENA - Unit WB 03 - Block I / Warehouse 11 - Airport FZE - P.O. Box 54592 - Dubai, U.A.E. - Tel.: +9714-29 94 009 - Fax: +9714-29 95 587 - E-mail: info@conrac.ae - www.conrac.ae

CONRAC LTDA Latin America - Carrera 14 # 96 - 82 - Bogotá - Colombia - Tel. / Fax: +57-1-34 65 338 - E-mail: info@conrac.com.co - www.conrac.com.co